

Carbon Dioxide Extinguisher

FBC2FF

2 kg (Fire Rating 34B)

FBC5

5 kg (Fire Rating 55B)



Flammable
Liquids



Electrical
Risks

Ideal for use on electrical equipment and used in contamination-sensitive places such as computer rooms, labs, food storage areas and processing plants. Also suitable in offices, factories or warehouses usually alongside a foam or water unit.

The 2 kg model FBC2FF is fitted with a Safe Swivel Horn which protects the user's hands against frost burn. Also improves the efficiency of the fire extinguisher.

The 5 kg model has a hose with the horn attached complete with its handle.

- ACCREDITED TO EN3 BY BSI AND KITEMARKED.
- 5 YEAR WARRANTY.
- STORED PRESSURE – EASY LOW-COST MAINTENANCE.
- ALUMINIUM BODY.
- SUITABLE FOR B CLASS AND ELECTRICAL FIRES.
- CONTROLLED DISCHARGE.
- FBC5 FITTED WITH FROST-FREE HORN.
- SUPPLIED WITH WALL-MOUNTING BRACKET.

Model	FBC2FF	FBC5
Capacity	2 kg	5 kg
Total Weight	5 kg	12.2 kg
Total Height	485 mm	675 mm
Total Width (incl. hose/horn)	180 mm	220 mm
Working Temp.	-30°C to +60°C	
Discharge Time / Temp.	9 secs	17 secs
Discharge Range.	2-3 m	
Operating Pressure	56 bar @ 20°C	
Minimum Burst Pressure	215 bar	