

AFFF Foam Extinguisher

FBF2

2 Litre (Fire Rating 5A / 34B)



Ideal for use in vehicles and in industrial / commercial premises. Widely used in taxis, mini-buses, buses and other passenger carrying vehicles. Also very effective on fires caused by the combustion of flammable liquids and materials that liquefy such as plastic, oils, greases, paints, tar...

Safe, if used in error, on live electrical equipment, since the spray is non-conductive and complies with dielectric test to EN3-7 clause 9. (Model tested to the BS EN3 35,000V dielectric test as defined by BSEN3-7:2004 + A1:2007).

- ACCREDITED TO EN3 BY BSI AND KITEMARKED.
- 5 YEAR WARRANTY.
- STORED PRESSURE – EASY LOW COST MAINTENANCE.
- SUITABLE FOR A AND B FIRE CLASSIFICATIONS.
- CONTROLLED DISCHARGE.
- SUPPLIED WITH POWDER COATED, STEEL WIRE BRACKET.

Model	FBF2
Capacity	2 Litre
Total Weight	3.97 kg
Total Height	420 mm
Total Width	160 mm
Working Temp.	+5°C to +60°C
Discharge Time	17 secs
Discharge Range	3-4 m
Operating Pressure	12 bar @ 20°C
Minimum Burst Pressure	55 bar