

AFFF Foam Extinguisher

FBF6

6 Litre (Fire Rating 13A / 144B)

FBF9

9 Litre (Fire Rating 21A / 183B)



Used in industrial and commercial premises, offices, petrol filling stations, chemical paint houses, boats, lorries. Also very effective on fires caused by the combustion of flammable liquids and materials that liquefy such as plastic, oils, greases, paints, tar....

Safe, if used in error, on live electrical equipment, since the spray is non-conductive and complies with dielectric test to EN3-7 clause 9. (Model tested to the BS EN3 35,000V dielectric test as defined by BSEN3-7:2004 + A1:2007).

- ACCREDITED TO EN3 BY BSI AND KITEMARKED.
- 5 YEAR WARRANTY.
- STORED PRESSURE – EASY LOW COST MAINTENANCE.
- SUITABLE FOR A AND B FIRE CLASSIFICATIONS.
- CONTROLLED DISCHARGE.
- SUPPLIED WITH POWDER COATED, STEEL WIRE BRACKET.

Model	FBF6	FBF9
Capacity	6 Litre	9 Litre
Total Weight	10.4 kg	14.5 kg
Total Height	550 mm	610mm
Total Width (excluding hose)	220 mm	230 mm
Working Temp.	+5°C to +60°C	
Discharge Time	30 secs	40 secs
Discharge Range	5-6 m	
Operating Pressure	12 bar @ 20°C	
Minimum Burst Pressure	55 bar	